

# RECESSED PRODUCT LINE 2021

TUNABLE/CIRCADIAN LIGHTING

RGBW LIGHTING




BIANCA 16W



BIANCA 14W



ROCKET 9W



VENUS 16W



RIVA 16W



10W RGBW



20W RGBW

FAMILY PRODUCT	BIANCA-16W-BI-RD BIANCA-16W-BI-SQ BIANCA-16W-BI-RDR BIANCA-16W-BI-RD-PTD				TB-SERIES VB1-SERIES VB2-SERIES S-Series				S-BR SERIES T-BR SERIES MR-BR SERIES V1-SERIES V2-SERIES				VENUS-BI18-40K-16W VENUS-BI27-65K-16W		V1-SERIES V2-SERIES C-SERIES		TB-SERIES VB1-SERIES VB2-SERIES S-Series		V1-SERIES V2-SERIES C-SERIES
WATTAGE	16W				14W				9W				16W		16W		10W		20W
CCT	1800K - 4000K		2700K - 6500K		1800K - 4000K		2700K - 6500K		1800K - 4000K		2700K - 6500K		1800K - 4000K	2700K - 6500K	1800K - 4000K	2700K - 6500K	RGB+White		RGB+White
BEAM ANGLE	20°	40°	20°	40°	20°	40°	20°	40°	20°	40°	20°	40°	40°	40°	40°	40°	20°	40°	40°
TOTAL LUMENS	1400 lm	1590 lm	1550 lm	1600 lm	1065 lm	1235 lm	1100 lm	1275 lm	600 lm	640 lm	620 lm	660 lm	995 lm	1155 lm	1590 lm	1600 lm	544 lm	500 lm	1058 lm
LED CRI	≥95Ra				≥95Ra				≥95Ra				≥95Ra		≥95Ra		≥95Ra (White chip only)		≥95Ra (White chip only)
LM RATING	LM-80				LM-80				LM-80				LM-80		LM-80		LM-80		LM-80
INPUT VOLTAGE	48 Volts RJ45				48 Volts RJ45				48 Volts RJ45				48 Volts RJ45		48 Volts RJ45		48 Volts RJ45		48 Volts RJ45
TRIM FINISH	Black and White				Black and White				Black and White				White		Black and White		Black and White		Black and White
LISTINGS	JA8 Tittle 24 (Only 2700K-6500K) cULus / E476753				JA8 Tittle 24 (Only 2700K-6500K) cULus / E476753				JA8 Tittle 24 (Only 2700K-6500K) cULus / E476753				cULus / E476753		JA8 Tittle 24 (Only 2700K-6500K) cULus / E476753		*Pending		cULus / E476753
IP GRADE	IP20 and IP65				IP20 and IP65				IP20 and IP65				IP20 Standard		IP20 and IP65		IP20 and IP65		IP20 and IP65
COMPATIBLE DRIVER	For dimming use DMX-SR2112				For dimming use DMX-SR2112				For dimming use DMX-SR2112				For dimming use DMX-SR2112		For dimming use DMX-SR2112		For dimming use DMX-SR2112		For dimming use DMX-SR2112
CEILING THICKNESS	½" to 1 ½" / 12.7mm to 38.1mm				½" to 1 ½" / 12.7mm to 38.1mm				½" to 1 ½" / 12.7mm to 38.1mm				Perfect fit into ceiling, takes up to 1/2" thick ceiling		½" to 1 ½" / 12.7mm to 38.1mm		½" to 1 ½" / 12.7mm to 38.1mm		½" to 1 ½" / 12.7mm to 38.1mm
LIFE SPAN	>50,000 Hours				>50,000 Hours				>50,000 Hours				>50,000 Hours		>50,000 Hours		>50,000 Hours		>50,000 Hours
WARRANTY	5 Years				5 Years				5 Years				5 Years		5 Years		5 Years		5 Years