



# SPECIFICATION SHEET

## TAPE-180-RGB+WW

### DESCRIPTION

- Fully dimmable and color controllable
- Double sided 3m tape backing
- Low power consumption
- Low heat emission
- Available in IP54
- Easy to install



Dimmable Lighting  
0 to 100% flicker free dimming



RGBW



Working Temperature



3 Year Limited  
Warranty



MODEL CODES	DESCRIPTION
TAPE-180-RGB+WW-IP54	Tape 180 LED/M, RGB+WW, 15.5W/M, 95+, 1022 Lm/M, 5M (16.4FT/Roll), 12mm, Dimmable, 24V, IP54



TAPE-180-RGB+WW-IP54



### SPECIFICATIONS

<b>LED Quantity:</b>	180 LED/M
<b>Color /CCT:</b>	RGB + WW
<b>Luminous Flux per meter/3.3FT:</b>	R:70Lm; G:130Lm; B:28Lm; 2700K:410Lm; 6500K:460Lm; RGB: 255 Lm; RGBW+WW:1095 Lm
<b>Power Rating per meter/3.3FT:</b>	15.5W, 24V, 0.6A
<b>CRI:</b>	Ra+95
<b>Bin/Step:</b>	1 bin, 3 step MacAdam
<b>Beam Angle:</b>	120°
<b>PCB Width:</b>	12mm
<b>Cut Length:</b>	100mm/4" or 18 LEDs
<b>IP Rating:</b>	IP54
<b>Max Run Length:</b>	5 meters (16.4FT/Roll)
<b>Lifespan:</b>	50,000 hrs
<b>Warranty:</b>	3 years
<b>Certificate:</b>	CE, RoHS, UL Listed
<b>Compatible Drivers:</b>	Use SR-2108A-M5, or DMX-SR2216 and PS-SR2216-96 driver/decoder
<b>Packaging:</b>	16.4 FT spool

### COLOR TEMPERATURE



### TYPICAL APPLICATIONS

- ✓ Accent lighting
- ✓ Decorative lighting
- ✓ Architectural lighting

### CUT LENGTH

18 LEDs/100mm




### COMPATIBLE TRACKS


\*For a dot-less result use one of these recommended track diffuser combinations.

\*\*Tapes with IP68 fit in tracks with an inner width of 15mm or more.


**TRACK-OP-002**




**TRACK-OP-004**




**TRACK-OP-008**




**TRACK-OP-010**




**TRACK-OP-011**




**TRACK-OP-013**




**TRACK-OP-014**



**TRACK-OP-035**




**TRACK-OP-036**




### COMPATIBLE TRIMLESS TRACKS

*\*For a dot-less result use one of these recommended trimless track diffuser combinations.*


**TRACK-OP-039-TL**




**TRACK-OP-040-TL**



**TRACK-OP-055-TL**



**TRACK-OP-056-TL**



**TRACK-OP-079-TL**

