

SPECIFICATION SHEET TEGA-IN-1-SERIES

TEGA-IN-1 SERIES - ACCENT LIGHTING





Dimmable Lighting



Tunable Lighting



RGBW Lighting



Working Temperature



3 Year Limited Warranty






1800K to 4000K

2200K to 5000K

2700K to 6500K

SPECIFICATIONS

Wattage	9 Watts	10 Watts
wattage) vvalts	10 Watts
Lumens Range	390Lm - 470 Lm	270 Lm
Beam Angle	20° and 40°	40°
LED CRI	≥95Ra	
Input Voltage	48 Volts, RJ45	
LED Type	CTM-9 /Luminus	
Housing material	Aluminum	
Dimensions	Ø65.50*H123 mm	
Certifications	cULus	
Compatible Decoder	DMX-SR2112	
Power Supply	PS-SR2112-96	
WorkingTemperature	-25C to 40C	
IP Grade	IP67	
Lifespan	50,000 Hours	




FRONT VIEW





DIMENSIONS




SPECIFICATION SHEET TEGA-IN-SERIES


PHOTOMETRIC INFORMATION / 20D

COLOR TEMPERATURE / 1800K - 4000K

Luminous Intensity Distribution Curve




Illuminance at a Distance




PHOTOMETRIC INFORMATION / 40D

COLOR TEMPERATURE / 1800K - 4000K

Luminous Intensity Distribution Curve



Illuminance at a Distance




SPECIFICATION SHEET TEGA-IN-1-SERIES


PHOTOMETRIC INFORMATION / 20D

COLOR TEMPERATURE / 2700K - 6500K

Luminous Intensity Distribution Curve




Illuminance at a Distance




PHOTOMETRIC INFORMATION / 40D

COLOR TEMPERATURE / 2700K - 6500K

Luminous Intensity Distribution Curve



Illuminance at a Distance






SPECIFICATION SHEET TEGA-IN-1-SERIES

PHOTOMETRIC INFORMATION / 40D

COLOR TEMPERATURE / RGBW

Luminous Intensity Distribution Curve



Illuminance at a Distance

