



## SPECIFICATION SHEET

# TAPE-240-RGB

### DESCRIPTION

- Fully dimmable and color controllable
- Double sided 3m tape backing
- Low power consumption
- Low heat emission
- Available in IP20
- Easy to install



**DL** Dimmable Lighting  
0 to 100% flicker free dimming



**RGB** RGB



**Working Temperature**  
-10°C to +40°C



**3 Year Limited Warranty**




**UL LISTED**

### SPECIFICATIONS

<b>LED Quantity:</b>	240 LED/M
<b>Color /CCT:</b>	RGB
<b>Chip:</b>	EPISTAR
<b>CRI:</b>	N/A
<b>Bin/Step:</b>	1 bin only, 4 step binning
<b>Luminous Flux per meter/3.3FT:</b>	1920-2400 Lm
<b>Beam Angle:</b>	120°
<b>Power Rating per meter/3.3FT:</b>	26.5W, 24V, 1.1A
<b>PCB Width:</b>	22mm
<b>Cut Length:</b>	25mm/0.99" or 6 LEDs
<b>IP Rating:</b>	IP20
<b>Max Run Length:</b>	5 meters (16.4FT/Roll)
<b>Lifespan:</b>	50,000 hrs
<b>Warranty:</b>	3 years
<b>Certificate:</b>	CE, RoHS, UL Listed
<b>Compatible Drivers:</b>	Use SRPC 2108-24V-200, SR-2108A-M5, or SR-2108B-M24 driver/decoder
<b>Packaging:</b>	16.4 FT spool IP20= 378g/roll

MODEL CODES	DESCRIPTION
TAPE-240-RGB	Tape 240 LED/M, RGB, 26.5W/M, 1940-2400Lm/Led, 5M (16.4FT/Roll), 22mm, Dimmable, 24V



### COLOR TEMPERATURE

RGB




### TYPICAL APPLICATIONS

- ✓ Accent lighting
- ✓ Decorative lighting
- ✓ Architectural lighting

### CUT LENGTH

25mm/0.99" or 6 LEDs



Find the cut line on the strip  
(between the solder pads).




Carefully cut the strip on the  
cut line.

[www.colorbeamlighting.com](http://www.colorbeamlighting.com)


### COMPATIBLE TRACKS / TRIMLESS TRACKS

*\*For a dot-less result use one of these recommended track / trimless tracks diffuser combinations.*


TRACK-OP-051




TRACK-OP-038-TL




TRACK-OP-028





TRACK-OP-056-TL




TRACK-OP-017



TRACK-OP-057-TL



TRACK-OP-080-TL



TRACK-OP-058-TL

