



# SPECIFICATION SHEET

## TAPE-240-RGB30K

### DESCRIPTION

- Fully dimmable and color controllable
- Double sided 3m tape backing
- Low power consumption
- Low heat emission
- Available in IP20
- Easy to install



Dimmable Lighting  
0 to 100% flicker free dimming



RGBW



Working Temperature




3 Year Limited  
Warranty



### SPECIFICATIONS

LED Quantity:	240 LED/M
Color /CCT:	RGB + 3000K
CRI:	Ra+95
Luminous Flux per meter/3.3FT:	1600 Lm
Beam Angle:	120°
Power Rating per meter/3.3FT:	26.5W, 24V, 1.1A
PCB Width:	22mm
Cut Length:	25mm/0.99" or 6 LEDs
IP Rating:	IP20
Max Run Length:	5 meters (16.4FT/Roll)
Lifespan:	50,000 hrs
Warranty:	3 years
Certificate:	CE, RoHS, UL Listed
Compatible Drivers:	Use SRPC 2108-24V-200, SR-2108A-M5, or SR-2108B-M24 driver/decoder
Packaging:	16.4 FT spool IP20= 378g/roll

MODEL CODES	DESCRIPTION
TAPE-240-RGB30K-IP20	Double Row Tape 240 LED/M, 5050 RGB+3000K, 20W/M,95+CRI, 1600Lm/M, 5M (16.4FT/roll), 22mm, 30Z PCB, 24V, IP20



### COLOR TEMPERATURE

RGB + 3000K




### TYPICAL APPLICATIONS

- ✓ Accent lighting
- ✓ Decorative lighting
- ✓ Architectural lighting

### CUT LENGTH

25mm/0.99" or 6 LEDs



Find the cut line on the strip  
(between the solder pads).




Carefully cut the strip on the  
cut line.

[www.colorbeamlighting.com](http://www.colorbeamlighting.com)


### COMPATIBLE TRACKS / TRIMLESS TRACKS

*\*For a dot-less result use one of these recommended track / trimless tracks diffuser combinations.*


TRACK-OP-051




TRACK-OP-038-TL




TRACK-OP-028





TRACK-OP-056-TL





TRACK-OP-017



TRACK-OP-057-TL



TRACK-OP-080-TL



TRACK-OP-058-TL

