

BALZO SERIES - SPOTLIGHT



1800K to 4000K

2200K to 5000K

2700K to 6500K

RGBW

SPECIFICATIONS


Wattage	10 Watts	14 Watts
Lumens Range	650 Lm	630 - 730 Lm
Beam Angle	20° and 40°	
LED CRI	≥95Ra	
Input Voltage	48 Volts, RJ45	
LED Type	CTM-9 /Luminus	
Housing material	Aluminum	
Dimensions	Ø76*H254.43mm	
Certifications	cULus	
Compatible Decoder	DMX-SR-2112 Decoder	
Power Supply	PS-SR2112-96 - Power Supply 96W	
Working Temperature	-25C to 40C	
IP Grade	IP68	
Lifespan	50,000 Hours	
Warranty	3 Year Limited Warranty	

PRODUCT CODES		
BALZO-V3-14W-BI-18-40K-20-BK	BALZO-V3-10W-RGBW-20-BK	
BALZO-V3-14W-BI-18-40K-40-BK	BALZO-V3-10W-RGBW-40-BK	
BALZO-V3-14W-BI-22-50K-20-BK		
BALZO-V3-14W-BI-22-50K-40-BK		
BALZO-V3-14W-BI-27-65K-20-BK		
BALZO-V3-14W-BI-27-65K-40-BK		

FRONT VIEW



DIMENSIONS



www.colorbeamlighting.com

450 Montee de Liesse Montreal, QC H4T 1N8 Tel: 844-301-CBNA (2262)

(2262) Email: info@colorbeamlighting.com


Colorbeam Lighting Inc. reserves the right to make changes in specifications and/or to discontinue any product at any time without notice or obligation and will not be liable for any consequences resulting from the use of this publication.




PHOTOMETRIC INFORMATION / 20D

COLOR TEMPERATURE / 1800K - 4000K

Luminous Intensity Distribution Curve




Illuminance at a Distance




PHOTOMETRIC INFORMATION / 40D

COLOR TEMPERATURE / 1800K - 4000K



Luminous Intensity Distribution Curve

Illuminance at a Distance



www.colorbeamlighting.com


Colorbeam Lighting Inc. reserves the right to make changes in specifications and/or to discontinue any product at any time without notice or obligation and will not be liable for any consequences resulting from the use of this publication.




PHOTOMETRIC INFORMATION / 20D

COLOR TEMPERATURE / 2700K - 6500K

Luminous Intensity Distribution Curve




Illuminance at a Distance



PHOTOMETRIC INFORMATION / 40D

COLOR TEMPERATURE / 2700K - 6500K



Luminous Intensity Distribution Curve

www.colorbeamlighting.com


Colorbeam Lighting Inc. reserves the right to make changes in specifications and/or to discontinue any product at any time without notice or obligation and will not be liable for any consequences resulting from the use of this publication.

Illuminance at a Distance





PHOTOMETRIC INFORMATION / 20D

COLOR TEMPERATURE / RGBW




Luminous Intensity Distribution Curve





PHOTOMETRIC INFORMATION / 40D

COLOR TEMPERATURE / RGBW



Luminous Intensity Distribution Curve

www.colorbeamlighting.com

Colorbeam Lighting Inc. reserves the right to make changes in specifications and/or to discontinue any product at any time without notice or obligation and will not be liable for any consequences resulting from the use of this publication.