

# SPECIFICATION SHEET **BALZO LG SERIES**

#### **BALZO LG SERIES - SPOTLIGHT**





Dimmable Lighting 0 to 100% flicker-free dimming



Tunable Lighting



RGBW Lighting



Working Temperature



3 Year Limited Warranty





1800K to 4000K

2200K to 5000K

2700K to 6500K

RGBW

#### **SPECIFICATIONS**


Wattage	9 Watts	10 Watts
Lumens Range	360 - 400 Lm	250 Lm
Beam Angle	40°	
LED CRI	≥95Ra	
Input Voltage	48 Volts, RJ45	
LED Type	CTM-9 /Luminus	
Housing material	Aluminum	
Dimensions	Ø50*H184.08mm	
Certifications	cULus	
Compatible De- coder	DMX-SR-2112 Decoder	
Power Supply	PS-SR2112-96 - Power Supply 96W	
Working Tem- perature	-25C to 40C	
IP Grade	IP68	
Lifespan	50,000 Hours	
Warranty	3 Year Limited Warranty	

# PRODUCT CODES BALZO-LG-9W-BR-18-40K-40-BK BALZO-LG-10W-RGBW-40-BK BALZO-LG-9W-BR-22-50K-40-BK BALZO-LG-9W-BR-27-65K-40-BK

#### **FRONT VIEW**



#### **DIMENSIONS**




www.colorbeamlighting.com

## **SPECIFICATION SHEET BALZO LG SERIES**

## PHOTOMETRIC INFORMATION / 40D


#### **COLOR TEMPERATURE / 1800K - 4000K**

#### Luminous Intensity Distribution Curve



Average Diffuse Angle(50%): 44.7°


#### Illuminance at a Distance




## PHOTOMETRIC INFORMATION / 40D

#### COLOR TEMPERATURE / 2700K - 6500K

#### Luminous Intensity Distribution Curve



#### Illuminance at a Distance






# SPECIFICATION SHEET **BALZO LG SERIES**

### PHOTOMETRIC INFORMATION / 40D

#### **COLOR TEMPERATURE / RGBW**

#### Luminous Intensity Distribution Curve



#### Illuminance at a Distance

