



SPECIFICATION SHEET

TAPE-256-BI-R1

DESCRIPTION

- Fully dimmable & tunable
- Double sided 3m tape backing
- Low power consumption
- Low heat emission
- Available in IP20
- Easy to install



Dimmable Lighting
0 to 100% flicker free dimming



Tunable Lighting



Working Temperature



3 Year Limited
Warranty



SPECIFICATIONS

LED Quantity:	256 LED/M
Color /CCT:	1800K-6500K
Chip:	EPISTAR
CRI:	90-95+
Luminous Flux per meter/3.3FT:	1600lm/m
Beam Angle:	120°
Power Rating per meter/3.3FT:	15W/m
PCB Width:	15mm
Cut Length:	62mm/2.5" or 16 LEDs
IP Rating:	IP20
Max Run Length:	5 meters (16.4FT/Roll)
Life Span:	50,000 hrs
Warranty:	7 years
Certificate:	CE, RoHS, UL Listed
Compatible Drivers:	Use SRPC 2108-24V-200, SR-2108A-M5, or SR-2108B-M24 driver/decoder
Packaging:	16.4 FT spool IP20= 378g/roll

MODEL CODES	DESCRIPTION
TAPE-256-BI-R1	Tape 256 LED/M, 2700K - 6500K, 14.4W/M, 95+, 1530Lm/M, 5M (16.4FT/Roll), 40mm, Dimmable, 24V



COLOR TEMPERATURE



TYPICAL APPLICATIONS

- ✓ Accent lighting
- ✓ Decorative lighting
- ✓ Architectural lighting